

Sensor/Actuator cable - SAC-17P-M23MS/2,0-35T/FS SHSCO - 1437384

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sensor/Actuator cable, 17-position, PUR/PVC, Black RAL 9005, shielded, Plug straight M23, A-coded, on Socket straight M12 SPEEDCON, A-coded, Cable length: 2 m

Product Features

- ✓ Easy and safe: 100% electrically tested plug-in components
- ✓ Save time, thanks to installation with SPEEDCON fast locking system
- ✓ Save space – with high-pos. connectors
- ✓ Reliable signal transmission – 360° shielding in environments with electromagnetic interference



Key commercial data

| | |
|--------------------------------------|-----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 293.7 GRM |
| Custom tariff number | 85444290 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|-----------------|-----|
| Length of cable | 2 m |
|-----------------|-----|

Ambient conditions

| | |
|---------------------------------|-----------------------------------|
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |
| | -40 °C ... 125 °C (Plug / socket) |
| Degree of protection | IP65 |
| | IP67 |

General

| | |
|-----------------------|-------|
| Rated current at 40°C | 1.5 A |
| Rated voltage | 30 V |

Sensor/Actuator cable - SAC-17P-M23MS/2,0-35T/FS SHSCO - 1437384

Technical data

General

| | |
|------------------------------|-------------------------------|
| Number of positions | 17 |
| Contact resistance | ≤ 5 mΩ |
| Insulation resistance | ≥ 100 MΩ |
| Coding | A - standard |
| Standards/regulations | M12 connector IEC 61076-2-101 |
| Status display | No |
| Protective circuit/component | Unwired |
| Surge voltage category | II |
| Pollution degree | 3 |
| Torque | 0.4 Nm (M12 connector) |

Material

| | |
|--------------------------|---------------------|
| Contact material | CuZn |
| Contact surface material | Ni/Au |
| Contact carrier material | PBT / PA 66 |
| Material of grip body | PUR |
| Material, knurls | Nickel-plated brass |

Cable

| | |
|------------------------------------|---|
| Cable type | Black PUR/PVC twisted pair |
| Cable type (abbreviation) | 35T |
| Conductor cross section | 0.14 mm ² |
| AWG signal line | 26 |
| Conductor structure signal line | 18x 0.10 mm |
| Core diameter including insulation | 1 mm ±0.05 mm |
| Wire colors | White-brown, green-yellow, gray-pink, blue-red, black-violet, gray/pink-red/blue, white/green-brown/green, white/yellow-yellow/brown-white/gray |
| Overall twist | Eight pairs around the filler to the core |
| Shielding | Tinned copper braided shield |
| Optical shield covering | 85 % |
| External sheath, color | Black RAL 9005 |
| External cable diameter | 9.20 mm |
| Number of bending cycles | 2000000 |
| Bending radius | 92 mm |
| Traversing path | 10 m |
| Traversing rate | 3 m/s |
| Acceleration | 10 m/s ² |
| Outer sheath, material | PUR |
| Material, inner sheath | PVC |

Sensor/Actuator cable - SAC-17P-M23MS/2,0-35T/FS SHSCO - 1437384

Technical data

Cable

| | |
|---------------------------------|---|
| Material conductor insulation | PVC |
| Conductor material | Tin-plated Cu litz wires |
| Conductor resistance | 142 Ω/km |
| Flame resistance | DIN VDE 0472 part 804, test type B |
| Resistance to oil | DIN VDE 0472 Part 803, test type B |
| Other resistance | Hydrolysis and microbe resistant as per VDE 0282 section 10 |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation) |
| | -5 °C ... 80 °C (cable, flexible installation) |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27060306 |
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |
| eCl@ss 5.1 | 27061801 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27061801 |
| eCl@ss 8.0 | 27061801 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001855 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC001855 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11 | 31251501 |
| UNSPSC 12.01 | 31251501 |
| UNSPSC 13.2 | 31251501 |

Approvals

Approvals

Approvals

GOST

Sensor/Actuator cable - SAC-17P-M23MS/2,0-35T/FS SHSCO - 1437384

Approvals

Ex Approvals


Approvals submitted

Approval details




Drawings

Schematic diagram



Plug pin assignment M23 plug, 17-pos., pin side view

Schematic diagram




Pin assignment M12, 17-pos., socket side view

Cable cross section



Black PUR/PVC twisted pair [35T]


Dimensioned drawing



M23 plug, straight, shielded


Sensor/Actuator cable - SAC-17P-M23MS/2,0-35T/FS SHSCO - 1437384

Dimensioned drawing



Socket M12-SPEEDCON, straight, shielded

Circuit diagram



Contact assignment of the M23 plug and the M12 socket