


1 2 3 4 5 6


A

Stiftkontakt
male contact



B

Buchsenkontakt
female contact



C

	Bestell-Nummer /PART NO versilbert /silverplated	φ	Leiterquerschnitt wire gauge		Abisolierlänge der Litze stripping length
			mm ²	AWG	
Stiftkontakt male contact	09 35 000 6103	1,15	0,5	20	6,0
	09 35 000 6104	1,3	0,75	18	
	09 35 000 6105	1,45	1,0	18	
	09 35 000 6106	1,75	1,5	16	
	09 35 000 6107	2,25	2,5	14	
Buchsenkontakt female contact	09 35 000 6203	1,15	0,5	20	6,0
	09 35 000 6204	1,3	0,75	18	
	09 35 000 6205	1,45	1,0	18	
	09 35 000 6206	1,75	1,5	16	
	09 35 000 6207	2,25	2,5	14	

D

All Dimensions in mm Original Size DIN A 4	Techn. Character.			Nicht tolerierte Maß/Free size tolerances	
		Dat.	Name	Maßstab/Scale 2:1	Han P Kontakte gedreht 16A Han P contacts turned 16A
	Detail.	10.11.10	ML		
	Insp.		Be		
	Stand.				
A	HARTING Electric GmbH & Co. KG			TB 09 35 000 6...	Blatt/ page
Mod.	Dat.	Name	D-32339 Espelkamp		
				Sub. f. TB 09 35 000 6... v. 28.03.07	