


## AVD75 Series

75 Watts

### Data Sheet

**Total Power:** 75 Watts  
**Input Voltage:** 36 - 75 V  
**# of Outputs:** Single



### SPECIAL FEATURES

- 2:1 Wide input range
- Optimised for high density, small space applications
- Low ripple and noise
- Fixed switching frequency
- High efficiency
- High capacitive load capability
- Pre-bias start-up capability
- Basic insulation system
- Through hole or SMT termination
- Openframe structure with baseplate option
- Two year warranty

### SAFETY

- UL, cUL: UL60950
- TUV/CE: IEC/EN60950

### Electrical Specifications

Input	
Input range	36 - 75 Vdc
Efficiency	92% @ 3.3 V; 84% @ 1.2 V
Output	
Voltage tolerance	+/-1.5%
Line regulation	0.2%
Load regulation	Single output: 0.5% @ 3.3 V; 0.25% @ 1.2 V
Noise/ripple	3.3 Vo: 70 mV 1.2Vo: 45 mV
Over voltage protection Over temperature protection	Auto-restart
Switching frequency	1.2V: 270 KHz, 3.3V: 250 KHz
Temperature coefficient	±0.02 /°C
Isolation	
I/O isolation:	1500 Vdc min.

### Environmental Specifications

Operating ambient temperature range	-40 °C to +85 °C
Storage temperature	-55 °C to +125 °C
Humidity	5% to 95% (non-condensing)
MTBF	2 Million hours
RoHS Compliant	

### Ordering Information

Model number	Input voltage	Output voltage	Power
AVD75-48S3V3-6L	36 - 75 V <sub>in</sub>	3.3 V @ 20 A	66 W
AVD75-48S3V3P-6L	36 - 75 V <sub>in</sub>	3.3 V @ 20 A	66 W
AVD75-48S3V3B-6L	36 - 75 V <sub>in</sub>	3.3 V @ 20 A	66 W
AVD75-48S3V3PB-6L	36 - 75 V <sub>in</sub>	3.3 V @ 20 A	66 W
AVD75-48S1V2TL	36 - 75 V <sub>in</sub>	1.2 V @ 25 A	30 W
AVD75-48S1V2-6L	36 - 75 V <sub>in</sub>	1.2 V @ 25 A	30 W
AVD75-48S1V2B-6L	36 - 75 V <sub>in</sub>	1.2 V @ 25 A	30 W

Notes:

Standard version is negative enable

-6 = 3.8 mm pin length



-T = Surface mount, reel tape package

-S = Surface mount, tray package

-L = RoHS 6 compliance

-P = Positive enable

### Mechanical Drawings



Notes:

1. All specifications are subject to change without notice. Mechanical drawings are for reference only.
2. Label and logo appearance may vary from what is shown on mechanical drawings.

UNIT: mm[inch]

BOTTOM VIEW: pin on upside

TOLERANCE: X.Xmm±0.5mm[X.XX in.±0.02in.]

X.XXmm±0.25mm[X.XXX in.±0.01in.]

## Pin Assignments

Pin #	Function
1	+V in
2	Enable
3	-V in
4	-V out
5	- Sense
6	Trim
7	+Sense
8	+V out

## WORLDWIDE OFFICES

### Americas

2900 S.Diablo Way  
 Tempe, AZ 85282  
 USA  
 +1 888 412 7832

### Europe (UK)

Waterfront Business Park  
 Merry Hill, Dudley  
 West Midlands, DY5 1LX  
 United Kingdom  
 +44 (0) 1384 842 211

### Asia (HK)

14/F, Lu Plaza  
 2 Wing Yip Street  
 Kwun Tong, Kowloon  
 Hong Kong  
 +852 2176 3333



[www.artesyn.com](http://www.artesyn.com)

Artesyn Embedded Technologies, Artesyn and the Artesyn Embedded Technologies logo are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. © 2016 Artesyn Embedded Technologies, Inc. All rights reserved. For full legal terms and conditions, please visit [www.artesyn.com/legal](http://www.artesyn.com/legal).

For more information: [www.artesyn.com/power](http://www.artesyn.com/power)  
 For support: [productsupport.ep@artesyn.com](mailto:productsupport.ep@artesyn.com)