

Electronic housing - UCS 145-125-F-GD-RPI 9005 - 1019720

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Complete housing for printed-circuit boards. Includes housing half shells, side panels with openings for all relevant connections, adhesive pads for affixing the Raspberry Pi model B2 and B3 computers, screws for housing and PCB attachment; black housing with turquoise-green corner inlays

Why buy this product

- High degree of application flexibility, thanks to the modular housing design
- Flexible PCB attachment, adapts to virtually all form factors
- Practical customization options
- Reduced logistics outlay, thanks to components which are compatible with one another

Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 507439
GTIN	4055626507439

Technical data

General

Housing type	Universal housings
Housing material	PC
Color (RAL)	black (9005)

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
---	------------------

Dimensions for the product

Height [h]	87 mm
Width [w]	125 mm
Depth [d]	47 mm

Standards and Regulations

Electronic housing - UCS 145-125-F-GD-RPI 9005 - 1019720


Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Drawings

Dimensional drawing



Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>