

## BC-500X10- 7 GN - 5454540

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Nominal current: 13.5 A, Nom. voltage: 400 V, Connection method: Screw connection with tension sleeve, Mounting: Wave soldering, Conductor/PCB connection direction: 0 °, Color: pastel green



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	2000 pc
Weight per Piece (excluding packing)	6.6 g
Custom tariff number	85369010
Country of origin	China

### Classifications

#### eCl@ss

eCl@ss 5.1	27260701
eCl@ss 6.0	27261101
eCl@ss 8.0	27440401
eCl@ss 9.0	27440401

#### ETIM

ETIM 4.0	EC002643
ETIM 5.0	EC002643

### Approvals

#### Approvals

#### Approvals

VDE Zeichengenehmigung / IEC EE CB Scheme / UL Recognized / cUL Recognized / cULus Recognized


#### Ex Approvals

# BC-500X10- 7 GN - 5454540


## Approvals

Approvals submitted


### Approval details

VDE Zeichengenehmigung 


mm <sup>2</sup> /AWG/kcmil	0.14-1.5
Nominal current I <sub>N</sub>	13.5 A
Nominal voltage U <sub>N</sub>	400 V

IECEE CB Scheme 

mm <sup>2</sup> /AWG/kcmil	0.14-1.5
Nominal current I <sub>N</sub>	13.5 A
Nominal voltage U <sub>N</sub>	400 V

UL Recognized 

	B	D
mm <sup>2</sup> /AWG/kcmil	30-14	30-14
Nominal current I <sub>N</sub>	10 A	10 A
Nominal voltage U <sub>N</sub>	300 V	300 V

cUL Recognized 

	B	D
mm <sup>2</sup> /AWG/kcmil	30-14	30-14
Nominal current I <sub>N</sub>	10 A	10 A
Nominal voltage U <sub>N</sub>	300 V	300 V

## BC-500X10- 7 GN - 5454540

### Approvals

