

Marker carriers - CARRIER-PMP (110X38) - 0831056

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Marker carriers, black, unlabeled, mounting type: Screws, rivets, lettering field size: 110 x 38 mm



Why buy this product

- ✓ The CARRIER-PMP (110x38) marker carrier is used in conjunction with insertable UC-PMP or PMP-RFID ... labels and PMT and PMST media marking labels.
- ✓ The CARRIER features snap-in pins which prevent the labels from falling out. In addition, the PMST (10x38) ... labels can be fixed in the carrier using the RVT-PA 3,5 BK fixing rivet.
- ✓ They can be mounted using screws, SCRT ... hose clips or WT cable binders.
- ✓ They are used to clearly identify devices and control cabinets.

Key Commercial Data

| | |
|------------------------|---|
| Packing unit | 10 STK |
| Minimum order quantity | 10 STK |
| GTIN |  4 046356 940870 |
| GTIN | 4046356940870 |

Technical data

Dimensions

| | |
|------------|--------|
| Length (b) | 110 mm |
| Width (a) | 38 mm |

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 105 °C |
|---------------------------------|-------------------|

General

| | |
|--|--------------------------------|
| Color | black |
| Components | free from silicone and halogen |
| Flammability rating according to UL 94 | V0 |
| Material | PA |

Marker carriers - CARRIER-PMP (110X38) - 0831056

Technical data

General

| | |
|-----------------------|----------------|
| RoHS compliant | Yes |
| Marking mounting type | Screws, rivets |

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>