

Standard Multilayer Ceramic Capacitors (Temperature compensating type)

TMK021CG4R1BK-W



■ Features

- Item Summary
4.1pF±0.1pF, 25V,
C0G/CG, 008004/0201 (EIA/JIS)
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping Embossed 50000pcs

■ Products characteristics table

Capacitance	4.1 pF ± 0.1pF
Case Size (EIA/JIS)	008004/0201
Rated Voltage	25 V
Q (min)	482 at 1MHz
Temperature Characteristic (EIA)	C0G
Operating Temp. Range (EIA)	-55 to +125 °C
Temperature Characteristic (JIS)	CG
Operating Temp. Range (JIS)	-55 to +125 °C
Temperature Characteristic	0 ±30 ppm/°C
High Temperature Loading (% Rated Voltage)	200 %
Insulation Resistance (min)	10 GΩ
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

■ External Dimensions

Dimension L	0.25 ±0.013 mm
Dimension W	0.125 ±0.013 mm
Dimension T	0.125 ±0.013 mm
Dimension e	0.0675 ±0.0275 mm





2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.

○TMK021CG4R1BK

25V 0201 CG/C0G 4.1pF +/- 0.1pF t=0.138mmMAX

25V 008004 CG/C0G 4.1pF +/- 0.1pF t=0.0054inchMAX



部品特性は設置環境、測定条件等により変化する場合があります。本データをご使用される際は実際の製品特性に対する参考データとしてご活用ください。また、本データは予告無く追加・削除及び変更を行う場合があります。ご注文の際は、納入仕様書のご確認をお願いします。

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.

TAIYO YUDEN reserves the right to make change to the data at any time without notice.

Before making final selection, please check product specification.