



NOTES:

1. INSERTION LOSS: 0.25 dB MAX.
2. OPERATION TEMP: -40 °C TO +80 °C.
3. MATERIALS:
 - ST2 ADAPTER:
 - BODY - ZINC ALLOY
 - RETENTION WASHER - BRASS, NICKEL PLATED
 - SLEEVE - CERAMIC, SINGLE-MODE
 - BRASS, MULTI-MODE
 - DUST CAPS - PVC
 - NUT - STEEL, NICKEL PLATED
 - LOCKWASHER - STAINLESS STEEL
 - FLANGE - ZINC ALLOY
4. THIS PRODUCT IS RoHS COMPLIANT.

PART NUMBER	ST2 ADAPTER SEE NOTE 3	DUST CAP COLOR	FLANGE FINISH
EHST2	SINGLE-MODE	RED	NICKEL
EHST2M	DOUBLE-MODE	BLACK	NICKEL
EHST2B	SINGLE-MODE	RED	BLACK CHROME
EHST2MB	DOUBLE MODE	BLACK	BLACK CHROME

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					FINISH			MATERIAL	
					SPEC No.			SPEC No.	
					FIRST USED ON		SCALE 1.5:1		
A	26306	12/1/08	RS	TJK	DATE DRAWN	BY	CHKD	APVD	Switchcraft®
REV	ECO NUMBER	DATE	BY	APVD	5/12/08	JGK	RS	TJK	
REVISIONS					DO NOT SCALE DRAWING				
					NAME			PART No.	
					E SERIES ST2 FIBER OPTIC ADAPTER			EHST2_SERIES	
								REV A	