



SPECIFICATION
MATERIAL
Features

This shell hood in poly-carbonate is supplied for top cable entry.

Following versions are available:

metallized,black and grey

The strain relief with two screws is attached separately.

Order Code

AGP - XX - G - X
1 2

1 No. of contacts
09, 15, 25, 37

2 Version
ME -Metallized
NEW -Plastic,black
NEW/GR -Plastic,Grey

Suitable knurled screws
AGP-RS/NEW
1 Set=2 pieces

- ⑤ **Material**
ABS
- Delivery includes**
- 2 half-sheels
- 2 fixing screws
- 4 screws
- 2 strain relief bow
- 2 nuts

Dimensions					
No.of contacts	A	B	C	D	E
09	31.0	25.0	40.2	20.5	8.0
15	39.6	33.4	35.8	27.7	8.1
25	55.0	46.5	42.0	40.8	8.2
37	69.3	63.5	50.9	57.8	10.0

RoHS compliant

Scale	1:1					Date	Name	Customer-No.
TOLERANCE		⑤	Corrected material	14.12.10	Dean	Drawn	12.01.2005	Ken
X.X	±X	④	Drawing revised	06.07.07	N.Schulz	Approved	14.12.2010	Gerber
X.XX	±X	③	Value E completed	03.08.05	Walter			
X.XXX	±X	②	Material completed	12.05.05	Walter			
DIM	TOL	①	Drawn	12.01.2005	Ken			
X.°	±X°							
X.X°	±X°							
Angle	TOL	Id.	Modification	Date	Name			



AGP xx G-x

Drawing-No.
ASS 0557 CO rev05

Replace Sheet