

APPLICATOR PARTS LIST

TYPE  
LENGTHWISE SPADE  
Ins. Piercing

AMP INCORPORATED  
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA		TERMINALS
1	WIRE CRIMPER			42				TO APPLY TERMINAL		42339
2	INS. CRIMPER 570322-8	1	386117	43				WIRE SIZE CRIMP HEIGHT		
3	ANVIL	1	374334	44						
4	ANVIL SPACER			45						
5	SHEAR BLADE	1	372270	46						
6	REAR SHEAR PLATE	1	379978	47						
7	SHEAR BLADE SPACER	2	372271	48						
8	FRONT SHEAR PLATE	1	372773	49						
9	REAR ANVIL SPACER PLT.			50						
10	FRONT ANVIL SPACER PLT.			51						
11	TOOL SPACER	1	370013	52						
12	CRIMP SPACER			53						
13	FRONT STRIP GUIDE	1	386283-1	54						
14	REAR STRIP GUIDE	1	386283-2	55						
15	RAM	1	471911	57						
16	TOOL HOLDER			58						
17	ADJ. CRIMP MOUNT			59						
18	ADJ. BLOCK			60	<del>MECH FEED ASSY 1 672185-2</del>					
19	APPLICATOR MOUNT <del>ASSY</del>	1	570656	61						
20	BASE PLATE			62						
21	BASE BLOCK			63						
22	STRIP GUIDE PLATE			64						
23	ANVIL HOLDER	1	370526	65	Tension Adj. Plate	1	374999			
24	AUX. ANVIL HOLDER	1	377515		MISCELLANEOUS					
25	STRIPPER	1	377037	66						
26	STRIPPER MOUNT	1	370660	67						
27	RETAINER PLATE	1	372251	68						
28	STRIPPER MOUNT BRACKET			69						
29	STRIPPER BUSHING			70						
30	STOCK DRAG	1	375381	71						
31	STOCK DRAG HANDLE	<del>1</del>	<del>375382</del>	72						
32	STOCK DRAG STUD 354045-1	2	<del>370589</del>		REV. REVISION RECORD	DATE	BY	ECN		
33	STOCK DRAG SPRING	2	1-23847-1		A SUPERSEDES 672185	4-10-69	RD/K	1-6605		
34	STOCK DRAG ADJ. SCREW	2	372997		A1 PER FCN	7-23-69	PK/WM	1-6337		
35	FEED FINGER HOLDER				B REV PER ECN	12-16-70	BS/A	1-7980		
36	FEED FINGER	1	375093		C REV PER ECN	3-19-75	WAS/G	1-9578		
37	FEED FINGER TIP				D REV PER FCN	8-26-73	AS/A	1-9699		
38	FEED FINGER SPACER				E ECN A-395892	9-92	M9/TB	-		
39	BASE CASTING	1	570238							
40	GUARD 457664-2	1	<del>470262</del>							
41										

CRIMPING DATA

TO APPLY TERMINAL: 42339

WIRE SIZE:      CRIMP HEIGHT:

CRIMP SIZE TYPE FEED

WIRE:      INSUL. .110      0      .656

SLEEVED:

INSULATION RANGE: .060 - .075      WIRE RANGE:

EXPLODED VIEW: A-6000      A-6000-1

REMARKS:

~~MECH FEED ASSY 1 672185-2~~

■ DENOTES WEARING PARTS  
RECOMMEND PURCHASE REPLACEMENT

THIS APPLICATOR IS TO BE USED ON  
AMP-O-LECTRIC 1-471273-3  
~~MISCELLANEOUS MECH FEED 572185-1~~

Alignment Gage 679597-2      DIST. 4

SERIAL NO.      DATE SHIPPED      DESIGNED:

CUSTOMER NAME AND ADDRESS      CHK'D:

APPLICATOR NUMBER: E      REV. 672185-1      SHEET 1 OF 1