


## DK-SERIES DKR 32 24VUC 1A

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



At just 6 mm wide, all components of the DKR minicouplers have an extremely narrow design. Weidmüller also offers 4 and 5 screw-connections, with a rated cross-section of 4 mm<sup>2</sup>.

The mini-coupler is suitable for a wide range of applications. It is used for the coupling of digital sensor/actuator signals with automation devices on the process level..

### General ordering data

Order No.	<a href="#">8008110000</a>
Type	DKR 32 24VUC 1A
Version	DK-SERIES, Relays, No. of contacts: 1, NO contact, Rh/Ru, Rated control voltage: 24 V UC ±10 %, Continuous current: 0.5 A, Screw connection
GTIN (EAN)	4008190014100
Qty.	10 pc(s).

**DK-SERIES**  
**DKR 32 24VUC 1A**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Ratings**

Conductor connection system	Screw connection	Humidity	40 °C / 93 % rel. humidity, no condensation
Open sides	right	Ambient temperature	-25 °C...+40 °C

**Dimensions and weights**

Width	6 mm	Height	75 mm
Depth	56 mm	Net weight	16.8 g

**Temperatures**

Operating temperature	-25 °C...+40 °C	Ambient temperature	-25 °C...+40 °C
Storage temperature	-40 °C...+60 °C		

**Connection data**

Clamping range, rated connection	4 mm <sup>2</sup>	Clamping range, rated connection, min.	0.5 mm <sup>2</sup>
Clamping range, rated connection, max.	4 mm <sup>2</sup>		

**Input**

Rated control voltage	24 V UC ±10 %	Rated current AC	15 mA
Rated current DC	9 mA	Power rating	0.36 VA / 216 mW
Response / drop-out voltage AC coil	12 V / 8 V	Pull-in (sparkover) / drop-out voltage DC coil	10 V / 11 V
Pull-in / drop-out current, AC coil	6.3 mA / 4.3 mA	Pull-in / drop-out current, DC coil	3.8 mA // 3 mA
Status indicator	Green LED		

**Output**

Max. switching voltage, AC	100 V	Continuous current	0.5 A
making current	500 mA	Max. switching power	10 W / 10 VA
Switch-on delay	typically 0.7...2.5 ms	Switch-off delay	typical. 0.2...2.0 ms
Response time	typ. 0.7...2.5 ms / 0.2...2 ms	Min. switching power	1 V / 1 mA
Max. switching frequency at rated load	5 Hz		

**Contact specifications**

No. of contacts	1	Contact design	NO contact
Contact material	Rh/Ru	Mechanical service life	10 <sup>9</sup> switching cycles

**Insulation coordination**

Rated voltage	150 V	Clearance and creepage distances for control side - load side	≥ 3 mm
Dielectric strength to mounting rail	4 kV <sub>eff</sub>	Impulse withstand voltage	1.5 kV
Protection degree	IP 20	Pollution severity	2
Surge voltage category	III		

**Other technical data**

Version	Relay coupler	Status indicator	Green LED
Free-wheel diode	No	Reverse polarity protection	not available

**DK-SERIES  
DKR 32 24VUC 1A**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data****Further details of approvals / standards**

Standards DIN EN 50178

**Classifications**

ETIM 2.0	EC001437	ETIM 3.0	EC001437
UNSPSC	30-21-19-17	eClass 4.1	40-02-06-14
eClass 5.1	27-37-16-01	eClass 6.0	27-37-16-01
eClass 7.0	27-37-16-01		

**Approvals**

Approvals

**Downloads**

Declaration of Conformity [K069\\_02\\_11.pdf](#)

**DK-SERIES  
DKR 32 24VUC 1A**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings****Electric symbol**