PART NUMBER	ITEM ① BODY	ITEM ② CONTACT	ITEM ③ INSULATOR
131-3701-801	BRASS GOLD PL .00001 MIN OVER NICKEL PL .00005 MIN OVER COPPER PL .00005 MIN	BRASS GOLD PL .00003 MIN OVER NICKEL PL .00005 MIN OVER COPPER PL .00005 MIN	TEFLON
131-3701-806	BRASS NICKEL PL .0001 MIN OVER COPPER PL .00005 MIN	BRASS GOLD PL .00003 MIN OVER NICKEL PL .00005 MIN OVER COPPER PL .00005 MIN	TEFLON



NOTES:

1. SPECIFICATIONS:

IMPEDANCE: 50 OHMS
FREQUENCY RANGE: 0-4 GHz
VSWR: NOT APPLICABLE
WORKING VOLTAGE: 335 VRMS MAX AT SEA LEVEL
DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS MIN AT SEA LEVEL
INSULATION RESISTANCE: 1000 MEGOHM MIN
CONTACT RESISTANCE:
CENTER CONTACT - INITIAL 6 MILLIOHM MAX, AFTER ENVIRONMENTAL 8 MILLIOHM MAX
OUTER CONDUCTOR - GOLD PLATED INITIAL 1 MILLIOHM MAX, AFTER ENVIRONMENTAL 1.5 MILLIOHM MAX
NICKEL PLATED INITIAL 2.5 MILLIOHM MAX, AFTER ENVIRONMENTAL 3.5 MILLIOHM MAX
BRAID TO BODY - NOT APPLICABLE
CORONA LEVEL: NOT APPLICABLE
INSERTION LOSS: NOT APPLICABLE
RF LEAKAGE: NOT APPLICABLE
RF HIGH POTENTIAL WITHSTANDING VOLTAGE: 600 VRMS AT 4 AND 7 MHZ

MECHANICAL:

ENGAGE/DISENGAGE FORCE: INITIAL 14 LBS MAX, AFTER DURABILITY 14 LBS MAX ENGAGEMENT, 2 LB MIN DISENGAGEMENT
MATING TORQUE: NOT APPLICABLE
COUPLING PROOF TORQUE: NOT APPLICABLE
COUPLING NUT RETENTION: NOT APPLICABLE
CONTACT RETENTION: 4 LBS MIN AXIAL FORCE
CABLE ACCEPTABILITY: NOT APPLICABLE
CABLE HEX CRIMP SIZE: NOT APPLICABLE
CABLE RETENTION: NOT APPLICABLE
DURABILITY: 500 CYCLES MIN

ENVIRONMENTAL:

(MEETS OR EXCEEDS THE APPLICABLE PARAGRAPH OF MIL-C-39012)
THERMAL SHOCK: MIL-STD-202, METHOD 107, CONDITION B
OPERATING TEMPERATURE: -65 DEG C TO 165 DEG C
CORROSION: MIL-STD-202, METHOD 101, CONDITION B
SHOCK: MIL-STD-202, METHOD 213, CONDITION B
VIBRATION: MIL-STD-202, METHOD 204, CONDITION B

DRAWING NO.
C - 131-3701-801/810

0	REVISIONS				
	CHANGED: REVISED AND REDRAWN. WAS "C" SIZE. DATED 2-27-86.				
03	04-04-88	EJ	RRF	RJB	05-12-88 ECO 23374
	ADDED: 2X .066+-.003. CHANGED: .066+-.006 WAS 2X .066 +-.003.				
04	10-31-88	EJ	RRF	RJB	11-3-88 ECO 23660
	ADDED: NOTE 2, REMARKS COLUMN CHANGED: .025+-.010 WAS .020+-.010, .068+-.006 WAS 2X .068+-.006				
5	10-20-92	RH	VTH	TAK	RAH	PAH	12-18-92 ECO 41339
	CHANGED: .068+-.007 WAS .068+-.006, UPDATED GRAPHICS				
6	1-27-94	RH	☒	TAK	☒	PAH	3-8-94 ECO 42143
	DELETED: P/N 131-3701-805, TIN DIP LEADS NOTE 2				
	* REVISION NUMBER FOLLOWED BY AN ALPHA * * CHARACTER INDICATES DRAWING CLARIFI- * * CATION OR PART NUMBER ADDITION ONLY. *				
6a	6-29-94	RH	☒	KHB			ECN 42508

CUSTOMER DRAWING

THIS DRAWING TO BE INTERPRETED PER ANSI Y 14.5M - 1982

"μSTATION"

COMPANY CONFIDENTIAL

TOLERANCE UNLESS OTHERWISE SPECIFIED	DRAWN BY EJ	DATE 8-3-87	JOHNSON a cinch connectivity solutions brand — Cinch Connectivity Solutions, 299 Johnson Ave. Ste. 100, Waseca, MN 56093, 1-800-247-8256
DECIMALS .XX ____ mm .XXX ____	CHECKED BY	DATE	TITLE JACK ASSEMBLY END LAUNCH SMB
MATL	APPROVED BY RRF	DATE 5-5-88	
FINISH	APPROVED BY RJB	DATE 5-9-88	CODE NO. / DRAWING NO. C - 131-3701-801/810
	RELEASE DATE	(10-14-86) 5-12-88	SCALE 10:1 / U/M INCH / SHEET 2 OF 2