

LC HEV FUSE

RoHS



Specifications

Interrupting Rating (10A, 15A, 20A, 30A):	10kA @ 450 VDC
Interrupting Rating (40A):	10kA @ 425 VDC
Voltage Rating (10A, 15A, 20A, 30A):	450 VDC
Voltage Rating (40A):	425 VDC
Operating Temperature Range:	-40°C to +125°C

Ordering Information

Part Number	Termination	Package Size
OHEVxxx.SXC	Cartridge	36
OHEVxxx.SXBD	Bolt Down	20
OHEVxxx.SXBDY	Blade	20

Description

The LC HEV fuse is designed for protection of high-voltage accessory circuits in electric and hybrid electric vehicles.

Time-Current Characteristics

% of Rating	Opening Time Min / Max (s) 10A	Opening Time Min / Max (s) 15A, 20A, 30A	Opening Time Min / Max (s) 40A
100	100 hrs / -	100 hrs / -	100 hrs / -
110	4 hrs / -	4 hrs / -	-
135	100 / 3600	150 / 3600	150 / 3600
150	10 / 1000	10 / 1000	10 / 1000
200	0.5 / 100	0.5 / 100	0.5 / 100
300	0.1 / 15	0.1 / 15	0.1 / 15
500	0.05 / 1	0.05 / 1	0.05 / 1

Ratings


Part Number	Current Rating	Color Code	Typical Voltage Drop at 70% I _R	Maximum Voltage Drop Spec at 100% IR	Cold Resistance	Minimum Melting I ² t
OHEV010.xxx	10A	Red	114 mV	300 mV	13.3 mOhm	255 A ² s
OHEV015.xxx	15A	Blue	96 mV	200 mV	7.9 mOhm	133 A ² s
OHEV020.xxx	20A	Yellow	79 mV	200 mV	6.4 mOhm	268 A ² s
OHEV030.xxx	30A	Green	67 mV	200 mV	2.7 mOhm	993 A ² s
OHEV040.xxx	40A	Orange	69 mV	200 mV	1.3 mOhm	1495 A ² s

Average Initial Measurements

LC HEV FUSE

RoHS

Time-Current Characteristic Curves



Dimensions

Dimensions in mm

