


LEAD FINISH: SILVER	
BUSHING FINISH: SILVER	
CAPACITANCE	1500pF
TEMP. RANGE	-55°C TO 125°C
CURRENT	3 AMP MAX.
WORKING VOLTAGE	125°C 200 VDC MAX
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
1	-
10	5
30	15
100	42
300	65
1GHz	70



MARKING:
 PART: SCI 726-001
 BAG: 51-726-001
 DATE CODE XXXX
 QTY/PACK XX
 (50/BAG MAX.)

	36	35	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	 SPECTRUM CONTROL INC.	ERIE, FAIRVIEW PENNSYLVANIA	
	CN 201445	CN 184882 REDRAWN	CHANGE NOTICE	Fractions $\pm 1/64$		Dwn.SLAGLE	Description FEED THRU RESIN SEAL FILTER
				Dec. .xx±		Ckd 5 / 1 / 01	
				Dec. .xxx±.010		Apvd.	
				Angles $\pm 0^{\circ} 30'$		Scale NONE	51-726-001
				CODE IDENT. NO. QLSP2			