

OptiMOS[®] -T2 Power-Transistor


Product Summary

V_{DS}	55	V
$R_{DS(on),max}$ (SMD version)	15.4	m Ω
I_D	45	A


Features

- N-channel - Enhancement mode
- Automotive AEC Q101 qualified
- MSL1 up to 260°C peak reflow
- 175°C operating temperature
- Green product (RoHS compliant)
- 100% Avalanche tested

PG-TO263-3-2 PG-TO262-3-1 PG-TO220-3-1



Type	Package	Marking
IPB45N06S3-16	PG-TO263-3-2	3N0616
IPI45N06S3-16	PG-TO262-3-1	3N0616
IPP45N06S3-16	PG-TO220-3-1	3N0616


Maximum ratings, at $T_j=25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current ¹⁾	I_D	$T_C=25\text{ °C}$, $V_{GS}=10\text{ V}$	45	A
		$T_C=100\text{ °C}$, $V_{GS}=10\text{ V}^{2)}$	33	
Pulsed drain current ²⁾	$I_{D,pulse}$	$T_C=25\text{ °C}$	90	
Avalanche energy, single pulse ²⁾	E_{AS}	$I_D=22.5\text{ A}$	145	mJ
Avalanche current, single pulse	I_{AS}		45	A
Gate source voltage ³⁾	V_{GS}		± 20	V
Power dissipation	P_{tot}	$T_C=25\text{ °C}$	65	W
Operating and storage temperature	T_j , T_{stg}		-55 ... +175	°C
IEC climatic category; DIN IEC 68-1			55/175/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics²⁾						
Thermal resistance, junction - case	R_{thJC}		-	-	2.3	K/W
Thermal resistance, junction - ambient, leaded	R_{thJA}		-	-	62	
SMD version, device on PCB	R_{thJA}	minimal footprint	-	-	62	
		6 cm ² cooling area ⁵⁾	-	-	40	

Electrical characteristics, at $T_j=25\text{ }^\circ\text{C}$, unless otherwise specified
Static characteristics

Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0\text{ V}, I_D=250\text{ }\mu\text{A}$	55	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=30\text{ }\mu\text{A}$	2.1	3	4	
Zero gate voltage drain current	I_{DSS}	$V_{DS}=25\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ }^\circ\text{C}$	-	0.1	1	μA
		$V_{DS}=25\text{ V}, V_{GS}=0\text{ V}, T_j=125\text{ }^\circ\text{C}^{1)}$	-	1	100	
Gate-source leakage current	I_{GSS}	$V_{GS}=20\text{ V}, V_{DS}=0\text{ V}$	-	1	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	$V_{GS}=10\text{ V}, I_D=23\text{ A}$	-	13.5	15.7	m Ω
		$V_{GS}=10\text{ V}, I_D=23\text{ A},$ SMD version	-	13.2	15.4	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Dynamic characteristics²⁾

Input capacitance	C_{iss}	$V_{GS}=0\text{ V}, V_{DS}=25\text{ V},$ $f=1\text{ MHz}$	-	2980	-	pF
Output capacitance	C_{oss}		-	450	-	
Reverse transfer capacitance	C_{rss}		-	430	-	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=27.5\text{ V},$ $V_{GS}=10\text{ V}, I_D=45\text{ A},$ $R_G=22\ \Omega$	-	28	-	ns
Rise time	t_r		-	61	-	
Turn-off delay time	$t_{d(off)}$		-	26	-	
Fall time	t_f		-	68	-	

Gate Charge Characteristics²⁾

Gate to source charge	Q_{gs}	$V_{DD}=11\text{ V}, I_D=45\text{ A},$ $V_{GS}=0\text{ to }10\text{ V}$	-	23	-	nC
Gate to drain charge	Q_{gd}		-	10	-	
Gate charge total	Q_g		-	43	57	
Gate plateau voltage	$V_{plateau}$		-	7.2	-	V

Reverse Diode

Diode continuous forward current	I_S	$T_C=25\text{ }^\circ\text{C}$	-	-	45	A
Diode pulse current ²⁾	$I_{S,pulse}$		-	-	90	
Diode forward voltage ²⁾	V_{SD}	$V_{GS}=0\text{ V}, I_F=45\text{ A},$ $T_j=25\text{ }^\circ\text{C}$	-	1.1	1.3	V
Reverse recovery time ²⁾	t_{rr}	$V_R=27.5\text{ V}, I_F=I_S,$ $di_F/dt=100\text{ A}/\mu\text{s}$	-	20	-	ns
Reverse recovery charge ²⁾	Q_{rr}		-	25	-	nC

¹⁾ Current is limited by bondwire; with an $R_{thJC} = 2.3\text{ K/W}$ the chip is able to carry 46A at 25°C. For detailed information see Application Note ANPS071E


²⁾ Defined by design. Not subject to production test.

³⁾ Qualified at -5V and +20V.

⁴⁾ Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm² (one layer, 70 μm thick) copper area for drain connection. PCB is vertical in still air.


1 Power dissipation

$P_{tot}=f(T_C); V_{GS} \geq 6 \text{ V}$



2 Drain current


$I_D=f(T_C); V_{GS} \geq 10 \text{ V}$



3 Safe operating area

$I_D=f(V_{DS}); T_C=25 \text{ °C}; D=0$


parameter: t_p



4 Max. transient thermal impedance

$Z_{thJC}=f(t_p)$


parameter: $D=t_p/T$



5 Typ. output characteristics

$I_D=f(V_{DS}); T_j=25\text{ }^\circ\text{C}$


parameter: V_{GS} , pulsed



6 Typ. drain-source on resistance

$R_{DS(on)}=f(I_D); T_j=25\text{ }^\circ\text{C}$


parameter: V_{GS}



7 Typ. transfer characteristics


$I_D=f(V_{GS}); V_{DS}=10\text{ V}$

parameter: T_j



8 Drain-source on-state resistance


$R_{DS(on)}=f(T_j); I_D=20\text{ A}; V_{GS}=10\text{ V}$



9 Typ. gate threshold voltage


$V_{GS(th)} = f(T_j); V_{GS} = V_{DS}$

parameter: I_D



10 Typ. capacitances


$C = f(V_{DS}); V_{GS} = 0 V; f = 1 MHz$



11 Forward characteristics of reverse diode

$I_F = f(V_{SD}), \text{pulsed}$


parameter: T_j



12 Typ. avalanche characteristics

$I_{AS} = f(t_{AV})$


parameter: $T_{j(start)}$



13 Typ. avalanche energy


$$E_{AS} = f(T_j)$$

parameter: I_D



15 Drain-source breakdown voltage


$$V_{BR(DSS)} = f(T_j); I_D = 1 \text{ mA}$$




14 Typ. gate charge

$$V_{GS} = f(Q_{gate}); I_D = 45 \text{ A pulsed}$$

parameter: V_{DD}



16 Gate charge waveforms



Published by
Infineon Technologies AG
81726 Munich, Germany

© Infineon Technologies AG 2007
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie"). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office. Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Revision History

Version	Date	Changes
Data Sheet 2.1	15.12.2006	Removal of ordering code
Data Sheet 2.1	15.12.2006	Implementation of avalanche current single pulse
Data Sheet 2.1	15.12.2006	Update of Infineon address
Data Sheet 2.1	15.12.2006	Removal of foot note 3, avalanche diagrams
Data Sheet 2.1	15.12.2006	Implementation of Qrr and trr typ
Data Sheet 2.1	15.12.2006	Pulse current rating from 180A to 90A
Data Sheet 2.1	15.12.2006	Update of disclaimer
Data Sheet 2.1	15.12.2006	Implementation of RoHS and AEC logo, update of feature list
Data Sheet 1.1	07.11.2007	Update of data sheet layout
Data Sheet 1.1	07.11.2007	Adaptation of Ias
Data Sheet 1.1	07.11.2007	implementation of footnote 2 for Eas specification
Data Sheet 1.1	07.11.2007	removal of Vdg specification from data sheet