

Datasheet for part number KJL7T13B35SNL

| Our Catalog Part Number: KJL7T13B35SNL | | |
|--|------------------|--|
| Our Global Manufacturing Part Number: 110930-0014 | | |
| Brand: Cannon Product Category: Circular Product Line: 38999 - | Style Series: KJ | |

| Product Datasheet | | |
|-----------------------------------|--|--|
| SERIES | 38999 - Style Series I | |
| STYLE | Jam nut receptacle | |
| CLASS | Environment resistant (without rear accessory) | |
| SHELL SIZE | 13 | |
| SHELL MATERIAL | Corrosion resistant shells of aluminum alloy | |
| INSULATOR MATERIAL | High grade plastic | |
| GROMMET AND SEAL MATERIAL | Silicone base elastomer | |
| PLATING | Olive drab cadmium over electroless nickel plate | |
| ARRANGEMENT | 13-35 | |
| NUMBER OF CONTACTS | 22 contacts size 22D | |
| GENDER | Socket | |
| CONTACT TYPE | Rear release crimp snap-in contacts | |
| CONTACT MATERIAL | Copper Alloy, gold plate | |
| POLARIZATION | 95° | |
| MOD. CONTACT | less contacts | |
| LOW PROFILE / LIGHT WEIGHT | no | |
| SCOOP PROOF | yes | |
| COUPLING SYSTEM | Bayonet | |
| ELECTROLYTIC EROSION | no | |
| DURABILITY (CYCLES) | 500 | |
| HIGH IMPACT SHOCK | yes | |
| EXTERNAL BENDING MOMENT (Size 25) | 650 in/lbs | |
| RANDOM VIBRATION "J" | Ambient | |
| SINE VIBRATION | 30 G, Ambient | |
| SAND, DUST, ICE | yes | |
| TEMPERATURE RANGE | 65°C (85°F) to + 175°C (+347°F) | |
| CORROSION RESISTANT | 500 hours | |
| TEST SERVICE RATING (MATED) | Sea Level = 1300 50000 ft. = 800 70000 ft. = 800 100000 ft. = 800 | |
| TEST SERVICE RATING (UNMATED) | Sea Level = 1300 50000 ft. = 550 70000 ft. = 350 100000 ft. = 200 | |
| OPERATING VOLTAGE | Vrms = 433 Vdc = 613 | |
| DISCLAIMER | Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML. | |