


# SCRH8D28

## SMD POWER INDUCTORS





### • Features

1. Magnetically shielded construction
2. Excellent Power Density
3. Engineered to Provide High Efficiency



## ELECTRICAL CHARACTERISTICS

Part Number	Inductance (uH) (1)	Test Frequency	DC Resistance (Ω MAX) (2)	Saturation Current <sup>(3)</sup> (A)	Temperature Current <sup>(4)</sup> (A)
SCRH8D28-2R5	2.5	100KHZ	15.6m	4.50	6.40
SCRH8D28-3R3	3.3	100KHZ	18.2m	4.00	4.80
SCRH8D28-4R7	4.7	100KHZ	24.7m	3.40	4.32
SCRH8D28-7R3	7.3	100KHZ	39m	2.80	3.60
SCRH8D28-100	10	100KHZ	47m	2.30	3.25
SCRH8D28-150	15	100KHZ	69m	1.90	2.80
SCRH8D28-220	22	100KHZ	99m	1.60	1.85
SCRH8D28-330	33	100KHZ	156m	1.30	1.66
SCRH8D28-470	47	100KHZ	195m	1.15	1.30
SCRH8D28-680	68	100KHZ	286m	0.95	1.17
SCRH8D28-101	100	100KHZ	430m	0.75	1.05



- (1). Inductance tolerance  $\pm 30\%$  tested at 0.25V, 0ADC and 25°C
- (2). DCR measured at 25°C.
- (3). The DC current at which the inductance decreases by 35% from its initial value.
- (4). The DC current that results in a 40°C temperature rise from 25°C ambient.

[Click here for QUANTITY PER REEL & PACKING INFORMATION](#)

Custom versions available upon request.

©2011 Signal Transformer – Specification subject to change without notice. 07.11