



General ordering data

Order No.	1062060000
Part designation	WTA 5/10
Version	Modular terminal, accessories, Test adapter
EAN	4008190020781
Qty.	5 pc(s).

Product notes

Note, technical data	Rated current 6 A
----------------------	-------------------

Additional technical data

Installation advice	Direct mounting
---------------------	-----------------

CSA rating data

Voltage (CSA)	300 V
CSA current	6 A

Conductors for clamping (additional connection)

Clamping range, max.	1 mm ²
Rated cross-section	0.75 mm ²

Conductors for clamping (rated connection)

Type of connection	Plug-in connection
No. of connections	1
Stripping length	6 mm
Solid, min.	0.5 mm ²
Solid, max.	1 mm ²
Flexible, min.	1 mm ²
Flexible, max.	1 mm ²
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm ²
Flexible with ferrule, max. (DIN 46228/1)	1 mm ²

Dimensions

Width	5 mm
-------	------

Dimensions

Height of lowest version	68.2 mm
Length	17 mm

Rating data

Rated cross-section	0.75 mm ²
Rated voltage	250 V
Rated current	6 A

Test adapter

Function	Test adapter
With snap-in pegs	Yes

Test adapter dimensions

Height with TS 35	68.2 mm
With snap-in pegs	Yes

Test adapter rated data

Rated voltage	250 V
---------------	-------

UL rating data

Voltage (UL)	300 V
Current (UL)	6 A

Approvals

Approvals institutes



Classifications

eClass 4.1	27-14-11-99
eClass 5.0	27-14-11-45
eClass 5.1	27-14-11-45

Similar products

Order No.	Part designation	Version
1051260000	WTA 5/1	Modular terminal, accessories, Test adapter