



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERMINAL NUMBERS FOR REF. ONLY
 4. RATING: 50mA @ 12VDC
 5. TRAVEL: 0.30±0.15mm
 - ▲ 6. OPERATING FORCE: 160±50mm
 7. CONTACT RESISTANCE: 100mΩ MAX.
 8. ELECTRICAL LIFE: 100,000 CYCLES
 9. ▲ DENOTES CRITICAL PARAMETER
 10. 2002/95/EC (ROHS) COMPLIANT

E-SWITCH®

TITLE TL1100AF160Q

| | | | | |
|-----|--------|-------------|----------|----|
| A | 20828 | RELEASED | 10/15/12 | rc |
| REV | PCR NO | DESCRIPTION | DATE | BY |

| | | | | |
|-------|------------|----|---------|-----|
| SCALE | DATE | DR | DWG | REV |
| 2:1 | 10/15/2012 | rc | P001096 | A |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED