



**NOTES:**

- METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
- INSULATORS: PBT GF UL 94 V-0; GREEN
- SIGNAL CONTACTS: COPPER ALLOY  
PLATING: GOLD FLASH over NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 20
- NO CONTACTS ON POS. A1 - A6
- CONNECTOR IS PART MARKED: 3013W6SAM99A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 2:1 (5:1)	
					material: see notes	
	date	name		title:		
	drawn 29.10.14	Henneboel		D-SUB COMBINATON FEMALE		
	appd. 29.10.14	Schmidt		13W6S		
norm			dwg no:		DIN-A3	
d-old			13K1A4798		sh: 1	
a Original			part no: 3013W6SAM99A10X			
rev.	description	date	name	<b>CONEC</b> <sup>®</sup>		