

Printed-circuit board connector - GMVSTBW 2,5/ 6-ST-7,62 BK - 1709895

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB connector, nominal current: 12 A, rated voltage (III/2): 630 V, number of positions: 6, pitch: 7.62 mm, connection method: Screw connection with tension sleeve, color: black, contact surface: Tin



The figure shows a 10-position version of the product

Why buy this product

- Well-known connection principle allows worldwide use
- Low temperature rise, thanks to maximum contact force
- Allows connection of two conductors
- Integrated double steel spring provides additional safety in the event of temperature and power fluctuations



Key Commercial Data

Packing unit	50 STK
GTIN	
GTIN	4055626139524

Technical data

Dimensions

Length [l]	12.52 mm
Width [w]	43.68 mm
Height [h]	26 mm
Pitch	7.62 mm
Dimension a	38.1 mm

General

Range of articles	GMVSTBW 2,5/...-ST
Type of contact	Female connector
Number of positions	6

Printed-circuit board connector - GMVSTBW 2,5/ 6-ST-7,62 BK - 1709895

Technical data

General

Connection method	Screw connection with tension sleeve
Insulating material group	I
Rated voltage (III/2)	630 V
Nominal current I _N	12 A
Nominal cross section	2.5 mm ²
Flammability rating according to UL 94	V0

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	--	---------