CONN SIZE	FILTER DESIGNATION	FILTER CIRCUITS	CAPACITANCE		3 dB MAX CUTOFF FREQ (MHz)	DIELECTRIC WITHSTANDING VOLTAGE	CONTACT RATING	CONTACT RESIST	WORKING VOLTAGE DC	MINIMUM INSERTION LOSS-DECIBELS (dB)							
			VALUE	TOLERANCE					−55°C TO +125°C	10 MHz	20 MHz	50 MHz	100 MHz	500 MHz	1 GHz	2 GHz	5 GHz
15	014	FT	1500pF	+30% −30%	2	300V	5A	.010 OHM MAX	100V	–	8	–	21	35	41	–	–





FILTER ELEMENT LOCATION



SOCKET VIEW

† ALL TEST CONDITIONS AT 25°C. 50% RELATIVE HUMIDITY.
CAP. PER MIL-STD-202 METHOD 305, 1.0 VRMS MAX. 1KHz.
D.W.V. PER MIL-STD-202 METHOD 301, 1-5 SEC. 50 mA MAX.
I.R. PER MIL-STD-202 METHOD 302.
I.L. PER MIL-STD-220, NO LOAD CONDITION.

NOTE:
SHELL: STEEL, TIN PLATED.
INSULATOR: UL 94V-O
CONTACT; COPPER ALLOY, .000015 GOLD PLATED IN SOCKET CONTACT MATING AREA.



THIS DOCUMENT CONTAINS PROPRIETARY INFORMATIONAND IS COPYRIGHTED. EXCEPT WITH THE WRITTEN PERMISSION OF SPECTRUM CONTROL INC., OR ITS SUBSIDIARIES, SUCH INFORMATION SHALL NOT BE PUBLISHED OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE AND THIS DOCUMENT SHALL NOT BE DUPLICATED IN WHOLE OR IN PART.

REV. NO.	CHANGE NOTICE
5	CN 211311
4	CN 199117

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES.

CADD SCALE: FULL
PLOT SCALE: 2x

TOLERANCES UNLESS OTHERWISE SPECIFIED
Fractions ± 1/64
Dec. .xx±
Dec. .xxx± .015
Angles ±0° 30'

CODE IDENT. NO. OLSP2

SPECTRUM CONTROL INC.
CONNECTOR PRODUCTS DIVISION
ERIE, PENNSYLVANIA

Dwn. KRDZALIC
Date 12/11/00
Engr. T.Taylor
Sheet 1 of 1

Description: 15 POSITION LOW PROFILE, SKT.RT.ANGLE FILTERED CONNECTOR

B | 56-514-014-GBL

Quality Products From The Specialists In Electro-Magnetic Compatibility