

# PIN RECEPTACLES

**FOR .015" - .020" DIAMETER PINS (#11 CONTACT)  
AND .015" - .022" DIAMETER PINS (#21 CONTACT)  
(SEE SPECIFIC CONTACT RANGE ON PAGE 251)**

<p><b>8467</b> 8467-0-15-XX-21-XX-04-0 Hex press-fit in .036 plated through-hole</p>	<p><b>6192</b> 6192-0-15-XX-21-XX-04-0 Square press-fit in .032 plated through-hole</p>	<p><b>9553</b> 9553-0-15-XX-X1-XX-04-0 Hex press-fit in .041 plated through-hole</p>	<p><b>5531</b> 5531-0-15-XX-21-XX-10-0 Hex press-fit in .041 plated through-hole</p>
<p><b>7553</b> 7553-0-15-XX-11-XX-10-0 Hex press-fit in .041 plated through-hole</p>	<p><b>9407</b> 9407-0-15-XX-11-XX-10-0 Solder mount in .040 min. mounting hole</p>	<p><b>9462</b> 9462-0-15-XX-21-XX-04-0 Hex press-fit in .043 plated through-hole</p>	<p><b>1147</b> 1147-0-18-XX-21-XX-10-0 Press-fit in .043 min. mounting hole Accepts wire sizes up to .014" dia.</p>
<p><b>3061</b> 3061-0-19-XX-21-XX-10-0 Wire Crimp Termination. Accepts wire sizes 28 AWG Max. / 32 AWG Min.</p>	<p><b>0579</b> 0579-0-15-XX-X1-XX-10-0 Press-fit in .040 mounting hole</p>	<p><b>8874</b> 8874-0-15-XX-11-XX-10-0 Bottom entry surface mount See page 152 for application details</p>	<p><b>0613</b> 0613-0-15-XX-21-XX-10-0 Press-fit in .047 mounting hole</p>

## SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Inches

**Tolerances On:** Lengths: ±.005

Diameters: ±.002

Angles: ± 2°



**ORDER CODE: XXXX - X - 1X - XX - XX - XX - 0**

**BASIC PART #**

**SPECIFY SHELL FINISH:**

01 200 μ" TIN/LEAD OVER NICKEL

◆ 80 200 μ" TIN OVER NICKEL (RoHS)

◆ 15 10 μ" GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

02 100 μ" TIN/LEAD OVER NICKEL

◆ 84 100 μ" TIN OVER NICKEL (RoHS)

◆ 27 30 μ" GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#11 or #21 CONTACT (DATA ON PAGE 251)**

(For alternate contact choices, see group A on page 248)

