




Material
 Contact Pin: Brass
 Insulator (housing): Thermoplastic (UL94V-0), Green
 Surface of solder tail: Tin plated

Electrical cULus / VDE
 Voltage rating: 300VAC / 300VAC
 Current rating: 8A / 10A
 Wire range:
 Solid wire (AWG):
 Wire strip length:
 Withstanding Voltage: 1.6KV / 2.5KV
 Operating temperature: -30°C to +105°C
 Soldering temperature: 250°C ± 10°C / 5 Sec
 Safety Approval:  

N= NUMBER OF CONTACTS

RoHS compliant

| | | | | | | | | | |
|-----------|-------|-----|--------------|------------|------|---|------------|---------|--|
| Scale | 1:1 | | | | | | Date | Name | Customer-No. |
| TOLERANCE | | | | | | Drawn | 10.12.2009 | Dean | ASSMANN WSW-No. A-TB381-VKxx |
| X. | ±0.50 | | | | | Approved | 10.12.2009 | Hellwig | |
| X.X | ±0.30 | | | | | | | | |
| X.XX | ±0.10 | | | | | | | | |
| DIM | TOL | | | | | | | | Drawing-No. |
| X.° | ±1° | | | | | | | | ASS 3840 CO |
| | | ① | Drawn | 10.12.2009 | Dean |  | | | rev01 |
| Angle | TOL | Id. | Modification | Date | Name | | | Replace | Sheet |



Drawing-No. **ASS 3840 CO** rev01

Replace Sheet