



- NOTES
- 1 ONE EXAMPLE OF THE ROTATION OF REF.NO. ⑥ TO REF.NO. ① IS SHOWN.
  - ② THE RECOMMENDED CLAMP TORQUE, REF.NO. ①: 2 TO 3N·m.
  - ③ THE RECOMMENDED CLAMP TORQUE, REF.NO. ②: 0.2 TO 0.3N·m.  
 LOCTITE 243, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF.NO. ①, ② FROM LOOSENING.
  - 4 THIS PRODUCTS TO BE USED WITH CABLE CLAMP, RM21WTP-CP\*(71).  
 \* DESIGNATE DIAMETER(mm) OF APPLICABLE CABLE.
  - 5 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER, DEPENDING ON THE CABLE STRUCTURE.  
 PLEASE CONFIRM BEFORE THE USE.

5	BRASS	NICKEL PLATING	10	CHLOROPRENE RUBBER	(BLACK)			
4	DIALLYL PHTHALATE	(BLACK) UL94V-0	9	BRASS	NICKEL PLATING			
3	DIALLYL PHTHALATE	(BLACK) UL94V-0	8	PHOSPHOR BRONZE	NICKEL PLATING			
2	COPPER ALLOY	SILVER PLATING 2μm min.	7	CHLOROPRENE RUBBER	(BLACK)			
1	BRASS	NICKEL PLATING	6	BRASS	NICKEL PLATING			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS			
UNITS	mm	SCALE	2 : 1	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
<b>HRS</b> HIROSE ELECTRIC CO., LTD.		APPROVED	: HY. KOBAYASHI	18.02.22	DRAWING NO.	EDC-110104-31-00		
		CHECKED	: HY. KOBAYASHI	18.02.22	PART NO.	RM21WTP-15P(31)		
		DESIGNED	: HY. KISHI	18.02.21	CODE NO.	CL109-1403-8-31		
		DRAWN	: MK. INOUE	18.02.13		1/1		