



- NOTES
- ① TOTAL LENGTH BECOMES 29.8±1 WHEN ⑧ IS SCREWED INTO ① COMPLETELY.
  - ② TABLE FOR ASSEMBLY AND SOLDERING IS AVAILABLE HR30-6P-3S-T01.
  - ③ THE RECOMMENDED CLAMP TORQUE OF REF. NO.⑧ TO BE 0.5N·m.  
 LOCTITE 263, LOCPRIMER 7649, HENKEL JAPAN IS RECOMMENDED TO PREVENT REF. NO.⑧ FROM LOOSENING.  
 SPACER FOR ASSEMBLY IS AVAILABLE HR30-6P-T02.
  - ④ SURFACE PLATING:GOLD PLATING 0.2µm min.  
 UNDER PLATING:NICKEL PLATING 2µm min.
  - ⑤ THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER,  
 DEPENDING ON THE CABLE STRUCTURE.  
 PLEASE CONFIRM BEFORE THE USE.

4	PBT	(BLACK)	UL94V-0	8	PBT	(BLACK)	UL94V-0		
3	SIR	(RED)		7	POLYACETAL	(NATURAL)			
2	PHOSPHOR BRONZE	④		6	CR	(BLACK)			
1	PPS	(BLACK)	UL94V-0	5	STAINLESS STEEL				
NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS		
UNITS	mm	⊕	SCALE	5 : 1	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
<b>HRS</b> HIROSE ELECTRIC CO., LTD.		APPROVED	HY. KOBAYASHI	18.03.12	DRAWING NO.		EDC-112005-31-00		
		CHECKED	HY. KOBAYASHI	18.03.12	PART NO.		HR30-6P-3S(31)		
		DESIGNED	DS. MATSUNE	18.03.12	CODE NO.		CL130-0004-1-31		
		DRAWN	DS. MATSUNE	18.03.12					