


**NETWORK CABLE SERIES 155431-1xxx**  
**Profibus DP 150Ω - 2x22AWG - shield - PUR jacket**  
**c  US Style 20233 (80°C / 300V)**

**1. CONSTRUCTION DATA**

**1.1 CONDUCTOR:**

Bare copper strand; according to EN 13602 - ETP1; stranding according to DIN VDE 0295, EN60228 Class 6  
Stranded lay compliant with UL 758.

**1.2 WIRE STRUCTURE:**

Nominal section (mm <sup>2</sup> )	AWG	Stranding (nbr of wires x wire diameter in mm)	Diameter of stranded core (mm)	Max Resistance Ref. std. IEC 60344 (Ω/km)
0.34	22	19x0.15	0.75	60.0

**1.3 INSULATION:**

Foam PE; Max Insulation resistance >200 MΩxkm (IEC60189-1&IEC60885-1 or EN50289-1-4); according to UL758,  
cores colors refer to Annex #1

**1.4 INSULATION DIAMETER**

Nominal section (mm <sup>2</sup> )	Nominal Ø (mm)	Nominal thickness (mm)
0.34	2.75	1.00

**1.5 ASSEMBLY:**

Cores stranded together, with two fillers between cores

**1.6 TAPE SHIELD:**

Aluminum/PET tape (Al face outside), nominal optical coverage 100%.

**1.7 BRAID SHIELD:**

Tin copper wire, nominal optical coverage 80%.

**1.8 TAPE:**

Over braid shield

**1.9 JACKET:**

Polyurethane (PUR, TPU), ether base, Halogen free, nominal hardness 90 Shore A; Silicone, Pb,Cd,Hg & FCKW free;  
according to UL758.

For overall diameter, jacket color refer to Annex #1.

REVISION HISTORY Rev.A 04/11/2015 RELEASED	ECR/ECN INFORMATION:	TITLE: <b>Profibus DP 150Ω – PUR jacket</b>	Page <b>1 of 3</b>
Document Number: <b>1554311004 PS P1E A</b>	Created/Revised by: <b>M. Arrigoni</b>	Checked by: <b>A. Defendi</b>	Approved by: <b>C. Lerosé</b>
THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION      Template: TDS REV.0 22/07/2015			

## 2. TECHNICAL DATA

### 2.1 ELECTRICAL:

Voltage rating 300 Vrms  
Voltage test on core 1500 Vrms x 1 min. (EN50395)

### 2.2 TEMPERATURE:

Temperature range (fixed) -40°C to +80°C  
Temperature range (flex) -20°C to +60°C (free motion without periodic recurrence and forced guidance)

### 2.3 CHEMICAL:

Oil resistance UL758/UL2556/EN50363-10-2 (7days @ 100°C - IRM902 oil)  
Free of FCKW, Silicone and Pb yes  
Halogen free yes (IEC60754-1 EN50267-2-1 VDE0472-815)

### 2.4 PHYSICAL:

UV resistant yes (UL1581/2556– 300h)  
Max installation pulling force 100N  
Bending radius (fixed) >10xOD  
Bending radius (flex) >15xOD  
Drag chain use (@ 20°C) >15xOD (up to 2Mio @ 20°C in a freely suspended chain)\*

\*Default criterium of the norm-bendings is electrical failure due to conductor breakage or conductor short-circuit. Extreme sheath adhesion is not a default criterium since it cannot be influenced by the cable manufacturer (e.g. through big abrasion between cable and chain, non-suitable chain construction or wrong installation of cable in the chain).

### 2.5 FLAME:

UL Vertical Flame Test pass  
UL VW-1, CSA FT-1 pass  
IEC 60332-1 pass  
IEC 60332-2 pass

## 3. COMPLIANCE

Accordance to:
 

- 2006/95/CE; 2004/108/CE; 2011/65/CE (RoHS)
- UL/CSA (UL AWM Style 20233, use: external interconnect of electronic equipment)

## 4. PRINTING & PACKAGE

Printing text Ink-jet type; conform to UL758  
Package available in different packaging sizes (refer to Annex #1)

REVISION HISTORY Rev.A 04/11/2015 RELEASED	ECR/ECN INFORMATION:	TITLE: <b>ProfiBUS DP 150Ω – PUR jacket</b>	Page <b>2 of 3</b>
Document Number: <b>1554311004 PS P1E A</b>	Created/Revised by: <b>M. Arrigoni</b>	Checked by: <b>A. Defendi</b>	Approved by: <b>C. Lerosé</b>
THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION Template: TDS REV.0 22/07/2015			

**ANNEX 1**

mm <sup>2</sup>	AWG	Number of conductors	Outer Diameter (mm)	Jacket color	Packaging size	Packaging composition	Standard order number	Sketch
0.34	22	2	8,20	Violet	S	1x200m	1554311004	 <p>Red-Green</p>
				Violet	M	1x500m	1554311005	
				Violet	L	1x1000m	1554311006	

REVISION HISTORY

Rev.A 04/11/2015 RELEASED

ECR/ECN INFORMATION:

TITLE:

**ProfiBUS DP 150Ω – PUR jacket**

Page

**3 of 3**

Document Number:

**1554311004 PS P1E A**

Created/Revised by:

**M. Arrigoni**

Checked by:

**A. Defendi**

Approved by:

**C. Lerosé**