


- NOTES:
1. SUGGESTED MOUNTING HOLE = ϕ .177
 2. HARDWARE IS INCLUDED

LEAD FINISH:	SOLDER
BUSHING FINISH:	SILVER
CAPACITANCE	2000pF MIN
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP MAX.
WORKING VOLTAGE	125°C 115 VAC MAX. 125°C 200 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.

NO LOAD INSERTION LOSS:

FREQ	IL
10MHz	8dB
100MHz	48dB
1GHz	70dB

SCHEMATIC




MARKING:

PART: S000 (FAIRVIEW)
S000M (MEXICO)

PACKAGE: SCI-3223-000
DATE CODE
QTY/BAG (200 MAX.)



8	7	6	5	4	3	2		REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED
CN 212860	CN 211467	CN 201766	CN 188080	CN 184923 ADDED METRIC DIM.	CN 184189	CN 182598	REDRAWN	CHANGE NOTICE	Fractions $\pm 1/64$
									Dec. .xx \pm
									Dec. .xxx \pm .010
									Angles $\pm 0^{\circ} 30'$
									CODE IDENT. NO. QLSP2



SPECTRUM CONTROL INC.

ERIE, FAIRVIEW
PENNSYLVANIA

Dwn. SLAGLE	Description Pi
Date 5/21/01	RESIN SEAL FILTER
Engr. T. Taylor	SCI-3223-000
Scale NONE	