


JKL LAMP PART NUMBER	COLOR 6900°KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (Cd/m ²)	*RATED LIFE (HRS)
CF20277-28B	x = .325 y = .295	1560 @ 0°C	625 @ 5mA	5.0 TYP.	38,000 TYP.	20,000 MIN. 40,000 AVG.

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
			DRAWN BY L. WENGSTROM		APP'VD BY DATE J.K. 4/22/04		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP		FSCM NO. 55335		DRAWING NO. CF20277-28B	
RELEASED & CANCEL P-0404-13			4/22/04		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 4/22/04		REVISION DATE	
REV. NO.	DESCRIPTION/ECO NUMBER		APP'VD DATE						REV. NO.		SHEET 1 of 1	