

2-Port HDMI to VGA + Audio Adapter / Splitter, 1920 x 1080 (1080p), TAA

MODEL NUMBER: P131-06N-2VA-U



Converts and splits an HDMI audio/video signal for display on 2 VGA monitors or projectors at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms.

Description

The P131-06N-2VA-U 2-Port HDMI to VGA + Audio Splitter converts and splits an HDMI audio/video signal for display on two VGA-enabled monitors or projectors at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms, this compact splitter features a built-in HDMI cable that connects to the source. It lets you use your existing VGA displays instead of buying new HDMI monitors or televisions.

The P131-06N-2VA-U supports video resolutions up to 1920 x 1080, including 1080p, as well as HDCP, EDID and 3D. The HDMI audio signal passes through the adapter and splits to two 3.5 mm stereo jacks. Orange LEDs next to each output port indicate whether the splitter is powered on and transmitting a signal to the connected displays.

The splitter works with all operating systems and is small enough to carry in your backpack or computer bag. Plug-and-play convenience means no software or drivers are needed. An included USB Micro-B cable connects between the source and the splitter to provide power, so no external power supply is required.

Features

Converts and Splits HDMI Signal to 2 VGA Displays at the Same Time

- Ideal for offices, conference rooms, retail settings, trade shows and classrooms
- Built-in HDMI cable connects to audio/video source
- Included USB Micro-B cable supplies power to splitter
- Save money by using existing VGA-enabled equipment

Highlights

- Supports video resolutions up to 1920 x 1080, including 1080p
- Included USB Micro-B cable supplies power to unit
- Works with all operating systems
- Plug and play—no software or drivers required
- Supports 3.5 mm stereo audio

System Requirements

- Computer, Blu-ray™ player or other source with HDMI output
- Available USB port or wall charger for power
- 1–2 displays with VGA input

Package Includes

- P131-06N-2VA-U 2-Port HDMI to VGA + Audio Splitter
- USB Micro-B cable, 3 ft.
- Owner's manual



Top-Shelf Performance

- Supports video resolutions up to 1920 x 1080, including 1080p
- Digital audio signal splits to dual 3.5 mm stereo audio jacks
- Complies with HDCP, EDID and 3D
- LEDs indicate whether splitter is powered on and transmitting signal to connected displays

Easy to Use Almost Anywhere

- Works with all operating systems
- Plug and play—no software, drivers or external power supply required
- Compact unit fits easily in backpack or computer bag

TAA-Compliant

- Complies with Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
UPC Code	037332196583
Technology	HDMI (All types); VGA/SVGA; Stereo Audio
INPUT	
Cable Length (ft.)	0.5
Cable Length (m)	0.15
Cable Length (in.)	6
Cable Length (cm)	15.24
PHYSICAL	
Shipping Dimensions (hwd / in.)	1.70 x 5.40 x 7.80
Shipping Dimensions (hwd / cm)	4.32 x 13.72 x 19.81
Shipping Weight (lbs.)	0.60
Shipping Weight (kg)	0.27
Color	Black
CONNECTIONS	
Side A - Connector 1	HDMI (MALE)
Side B - Connector 1	(2) HD15 (FEMALE)
Side B - Connector 2	(2) 3.5MM (FEMALE); HD15 (FEMALE)



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty
Product Warranty Period (U.S. & Canada)	1-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>