

PIN RECEPTACLES

FOR .015" - .025" DIAMETER PINS

<p>4011 4011-0-15-XX-30-XX-04-0 Press-fit in .057 mounting hole</p>	<p>1801 1801-0-15-XX-30-XX-04-0 Press-fit in .057 mounting hole. Shell is Phosphor Bronze Alloy 544 (B2)</p>	<p>1001 1001-0-15-XX-3X-XX-04-0 Press-fit in .057 mounting hole</p>	<p>0156 0156-0-18-XX-30-XX-04-0 Self-retention socket pin .038 - .043 hole prior to soldering</p>												
<p>0255 0255-0-15-XX-30-XX-04-0 Solder mount in .022 min. mounting hole</p>	<p>1109 1109-0-15-XX-30-XX-04-0 Hex press-fit in .057 plated through-hole</p>	<p>3013 3013-0-15-XX-32-XX-04-0 Press-fit in .057 mounting hole</p>	<p>0134 0134-0-15-XX-3X-XX-04-0 Press-fit in .057 mounting hole</p>												
<p>0132/0135 013X-0-15-XX-30-XX-04-0 Press-fit in .057 mounting hole</p> <table border="1" data-bbox="511 1344 730 1491"> <thead> <tr> <th>Basic Part Number</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>0132-0</td> <td>.273</td> </tr> <tr> <td>0135-0</td> <td>.183</td> </tr> </tbody> </table>		Basic Part Number	Length A	0132-0	.273	0135-0	.183	<p>0133/0147 01XX-0-15-XX-30-XX-04-0 Press-fit in .059 mounting hole</p> <table border="1" data-bbox="1209 1344 1429 1491"> <thead> <tr> <th>Basic Part Number</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>0133-0</td> <td>.382</td> </tr> <tr> <td>0147-0</td> <td>.563</td> </tr> </tbody> </table>		Basic Part Number	Length A	0133-0	.382	0147-0	.563
Basic Part Number	Length A														
0132-0	.273														
0135-0	.183														
Basic Part Number	Length A														
0133-0	.382														
0147-0	.563														

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard
Contact Material: Beryllium Copper Alloy 172, HT
Dimensions: Inches
Tolerances On: Lengths: ±.005
 Diameters: ±.002
 Angles: ± 2°



ORDER CODE: XXXX - X - 15 - XX - XX - XX - 10 - 0

BASIC PART #

- SPECIFY SHELL FINISH:**
- 01 200 μ" TIN/LEAD OVER NICKEL
 - ◆ 80 200 μ" TIN OVER NICKEL (RoHS)
 - ◆ 15 10 μ" GOLD OVER NICKEL (RoHS)

- SPECIFY CONTACT FINISH:**
- 02 100 μ" TIN/LEAD OVER NICKEL
 - ◆ 84 100 μ" TIN OVER NICKEL (RoHS)
 - ◆ 27 30 μ" GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#30 or #32 CONTACT (DATA ON PAGE 253)
 (For alternate contact choices, see groups B and C on page 248)

