CONN SIZE	FILTER DESIGNATION	FILTER CIRCUITS	CAPACITANCE VALUE	CAPACITANCE TOLERANCE	3 dB MAX CUTOFF FREQ (MHz)	DIELECTRIC WITHSTANDING VOLTAGE	CONTACT RATING	CONTACT RESIST	WORKING VOLTAGE DC −25°C TO +125°C	MINIMUM INSERTION LOSS-DECIBELS (dB) 20 MHz	100 MHz	500 MHz	1 GHz
25	014	FT	1500pF	+30% −30%	2	300 V	5 AMPS	.010 OHM MAX	100 VDC	8	21	35	41



NOTES:

1. SHELL: STEEL, TIN PLATE
2. INSULATORS: UL94V-0
3. CONTACTS: COPPER ALLOY: .000030 GOLD IN SOCKET CONTACT MATING AREAS





THIS DOCUMENT CONTAINS PROPRIETARY INFORMATIONAND IS COPYRIGHTED. EXCEPT WITH THE WRITTEN PERMISSION OF SPECTRUM CONTROL INC., OR ITS SUBSIDIARIES, SUCH INFORMATION SHALL NOT BE PUBLISHED OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE AND THIS DOCUMENT SHALL NOT BE DUPLICATED IN WHOLE OR IN PART.

REV. NO.	CHANGE NOTICE
8	CN 207444
7	CN 205178
6	CN 205079
5	CN 199113

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES.

CADD SCALE: FULL
PLOT SCALE: 2x

TOLERANCES UNLESS OTHERWISE SPECIFIED
Fractions ± 1/64
Dec. .xx±
Dec. .xxx± .015
Angles ±0° 30'

CODE IDENT. NO. 33095

SPECTRUM CONTROL INC.
CONNECTOR PRODUCTS DIVISION
ERIE, PENNSYLVANIA

Dwn. KRDZALIC
Date 6/10/02
Apvd. K WOOD
Sheet 1 of 1

Description: 25 POSITION LOW PROFILE,SOCKET/PCB TAIL FILTERED CONNECTOR

B 56-523-014-TI

Quality Products From The Specialists In Electro-Magnetic Compatibility