

# Components of electronic housing - UM-PRO PE CONTACT L3 - 2200163

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PE contact for UM-PRO panel mounting base for connecting the PCB to the DIN rail at level 3

The figure shows the versions for PCB level 1

## Product Features

- Plug-in assembly reduces assembly time and therefore saves costs
- Mounting close to the edge provides wiring advantages
- Freely positionable covers offer flexibility
- PE contacts that can be fitted on both sides ensure safety
- Additional foot elements increase mechanical stability
- Temperature range up to 100°C extends the possible fields of application (UM-PRO)
- Device communication can be extended by BUS cross contacting
- Additional labeling of PCB with Phoenix Contact PMB module marker carrier (drill hole diameter 4 mm)
- Well-designed profile geometry increases the form stability

## Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	3.0 GRM
Custom tariff number	85369085
Country of origin	Germany

## Technical data

Product type	Ground contact
--------------	----------------

## Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506

## Components of electronic housing - UM-PRO PE CONTACT L3 - 2200163

### Classifications

#### eCl@ss

eCl@ss 5.1	27180506
eCl@ss 6.0	27400603
eCl@ss 7.0	27182701
eCl@ss 8.0	27182701

#### ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC000275
ETIM 5.0	EC000275

#### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501