

**DESCRIPTION: 2MM SINGLE ROW RECEPTACLE**

"L" = NO. OF CONTACTS PER ROW X .079

**MATERIAL:**  
 HOUSING: NYLON 6T (UL 94V-0) BLACK  
 CONTACT: PHOSPHOR BRONZE  
 PLATING: GOLD FLASH ENTIRE CONTACT  
 RoHS COMPLIANT

**ELECTRICAL:**  
 CURRENT RATING: 1 AMP  
 CONTACT RESISTANCE: 20 mOHM MAX.  
 INSULATOR RESISTANCE: 5000 MEGOHMS MIN.  
 DWV: 500V AC  
 OPERATING TEMP:  
 -40°C TO +105°C  
 PROCESS TEMP.: 260°C FOR 10 SECONDS



**SERIES** \_\_\_\_\_ 2563 YY 01RP2  
 2563 = SINGLE ROW

**POSITIONS** \_\_\_\_\_  
 SINGLE - INCREMENTS OF 1  
 (03 TO 40)

**TYPE:** \_\_\_\_\_  
 01 = STRAIGHT

**PLATING:** \_\_\_\_\_  
 P2 = GOLD FLASH

	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.		DRAWN: PAM JENKINS	DATE: 1-30-06
	NorComp		CHECKED:	DATE:
SCALE: NTS			SHEET 1 OF 1	REV 1
DWG NO.			2563YY01RP2	