




LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
J		EC 0G3C 0759 04		01FEB05	BSV	JLG	
J1		REVISED PER ECO-09-020689		02SEP09	KK	AEG	



- 1 CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- 2 USE WITH #26-#30 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- 3 THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 FOR INDIVIDUAL ASSEMBLIES SEE PART NUMBER 103649
- 6 ASSEMBLIES ARE JOINED BY THE CARRIER STRIP. ORDER QUANTITY REFLECTS TOTAL NUMBER OF INDIVIDUAL ASSEMBLIES REQUIRED. SEE TABLE FOR NUMBER OF ASSEMBLIES PER STRIP.
- 7 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE BEAMS)
- 8 MAXIMUM ALLOWABLE BOW OF ASSEMBLY NOT TO EXCEED .055.
- 9 CONTACTS: .000015 GOLD IN THE CONTACT AREA, .000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA, ALL OVER .000050 NICKEL
- 10 CONTACTS: .000015 GOLD IN THE CONTACT AREA, .000050-.000100 MATTE TIN ON THE TERMINATION AREA, ALL OVER .000050 NICKEL
- 11 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



11	10	2	2.40	1.198	1-103648-1	12	6-103972-1
11	10	2	2.20	1.098	1-103648-0	11	6-103972-0
11	10	2	2.00	.998	103648-9	10	5-103972-9
11	10	2	1.80	.898	103648-8	9	5-103972-8
11	10	2	1.60	.798	103648-7	8	5-103972-7
11	10	2	1.40	.698	103648-6	7	5-103972-6
11	10	4	2.39	.598	103648-5	6	5-103972-5
	10	4	1.99	.498	103648-4	5	5-103972-4
	10	5	1.99	.398	103648-3	4	5-103972-3
	10	8	2.40	.298	103648-2	3	5-103972-2
	10	10	2.00	.198	103648-1	2	5-103972-1
11	9	2	2.40	1.198	1-103648-1	12	1-103972-1
11	9	2	2.20	1.098	1-103648-0	11	1-103972-0
11	9	2	2.00	.998	103648-9	10	103972-9
11	9	2	1.80	.898	103648-8	9	103972-8
11	9	2	1.60	.798	103648-7	8	103972-7
11	9	2	1.40	.698	103648-6	7	103972-6
11	9	4	2.39	.598	103648-5	6	103972-5
	9	4	1.99	.498	103648-4	5	103972-4
	9	5	1.99	.398	103648-3	4	103972-3
	9	8	2.40	.298	103648-2	3	103972-2
	9	10	2.00	.198	103648-1	2	103972-1
	6	B	A	HOUSING PART NUMBER	NO OF POSN	ASSEMBLY PART NUMBER ON STRIP	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN L. MAYER 05 NOV 1986
 CHK P.C.DEJONG 12-11-86
 APVD 13-11-86

TOLERANCES UNLESS OTHERWISE SPECIFIED:
 0 PLC ± -
 1 PLC ± -
 2 PLC ± .02
 3 PLC ± .005
 4 PLC ± -
 ANGLES ± -
 FINISH SEE TABLE

HOUSING: FLAME RETARDANT THERMOPLASTIC, COLOR:BLACK, CONTACTS: PHOS BRONZE

NAME RCPT ASSY, AMPMODU MTE, SINGLE ROW, .100 CL, WITH GUIDE RIBS, FOR #26-#30 AWG WIRE SIZE, STRIP FORM

PRODUCT SPEC 108-25034
 APPLICATION SPEC 114-25026

WEIGHT -

CUSTOMER DRAWING

Tyco Electronics Corporation Harrisburg, Pa 17105-3608

SIZE A2 CAGE CODE 00779 DRAWING NO C=103972 RESTRICTED TO -

SCALE 4:1 SHEET 1 OF 1 REV J1