



**Part Number: 6100UH**

Security & Sound, 2 Conductor 14 AWG TC, Plenum

## Product Description

Security & Commercial Audio Cable, 2 Conductor 14 AWG stranded (19x27) tinned copper conductors with Flamarrest® insulation, Plenum, Flamarrest® jacket with ripcord.

## Technical Specifications

### Product Overview

Environmental Space:	Indoor - Plenum
Suitable Applications:	Intercom/PA Systems, Sound/Audio Systems

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors
14	19x27	TC - Tinned Copper	2

Conductor Count:	2
Conductor Size:	14 AWG

#### Insulation

Material	Material Trade Name	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.011 in

#### Color Chart

Number	Color
1	Black
2	White

#### Outer Shield Material

Material
Unshielded

#### Outer Jacket Material

Material	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	0.015 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
2.53 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	
36 pF/ft	
Shielding:	Unshielded

#### Inductance

Nominal Inductance
0.145 µH/ft

## Current

### Max. Recommended Current [A]

Per conductor @ 25°C ambient: 8 A

## Voltage

### UL Voltage Rating

150 V RMS

## Temperature Range

Installation Temp Range:	0°C To +75
UL Temp Rating:	75°C
Operating Temp Range:	-10°C To +75°C

## Mechanical Characteristics

Bulk Cable Weight:	38 lbs/1000ft
Max Recommended Pulling Tension:	95 lbs
Min Bend Radius/Minor Axis:	2.5 in

## Standards

NEC Articles:	725
NEC/(UL) Specification:	CL2P

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes

## Suitability

Suitability - Indoor:	Yes
-----------------------	-----

## Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262
UL voltage rating:	150 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

## Part Number

Non-Plenum Number:	5100UH
--------------------	--------

## Variants

Item #	Color
6100UH 010U1000	Black
6100UH 008U1000	Gray
6100UH 8771000	Natural
6100UH 877U1000	Natural
6100UH 009U1000	White

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product

Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.