



- 1 CIRCUIT NO.1 IS AMPMARK SIDE.
- △ MATERIAL: HOUSING, 66 NYLON (GF), BLACK.
- △ CONTACT, PHOSPHOR BRONZE.
- △ FINISH: Au AT CONTACT AREA (SEE TABLE), MATTE TIN PLATED AT TINE, OVER Ni UNDER PLATED ALL OVER.
- △ FOR SECURING CONNECTOR, USE CROSS RECESSED PAN HEAD TAPPING SCREW CLASS 2, M3x8mm. (SCREW-IN TORQUE TO BE 39.2N (4kgf)-cm MAX.)

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE: 24MAR80	
DESIGNER: COREL WANG	24MAR80	DATE: 24MAR80	24MAR80
PRODUCT SPEC: 108-60044	24MAR80	DATE: 24MAR80	24MAR80
APPLICATION SPEC:		DATE: 24MAR80	24MAR80
WEIGHT:		DATE: 24MAR80	24MAR80
CUSTOMER DRAWING:		DATE: 24MAR80	24MAR80
GENERAL TOLERANCE	10 ±: ±0.2	DATE: 24MAR80	24MAR80
	30 ±: > 10: ±0.25	DATE: 24MAR80	24MAR80
	100 ±: > 30: ±0.3	DATE: 24MAR80	24MAR80
	ANGLES: ±3°	DATE: 24MAR80	24MAR80