



**NOTES:**

**MATERIAL**

- 1. Insulator Material: PBT+30%G.F (UL94V-0), Gray
- 2. Contact Material : Brass
- 3. Contact Plating : Au or Sn Over Ni

**ELECTRICAL**

- 1. Current Rating : 3.0AMP
- 2. Withstand Voltage : 500V AC/DC
- 3. Contact Resistance : 20mΩ max
- 4. Insulation Resistance: 1000MΩ min

**ENVIRONMENTAL**

- 1. Operation Temperature: -40°C to +105°C
- 2. Packing : Tray

08~16 Pin without "A"

Ordering Information

xx: No. of Contacts (08,10,14,16,20,24,26,30,34,40,50,60,64)

⑤ Wire Spec: AWG28

**RoHS compliant**  
Unit: mm



Scale	Free						Date	Name	Customer-No.
TOLERANCE		⑤	Add wire spec	14.02.2014	Amy	Drawn	25.01.2006	Alex	ASSMANN WSW-No. <b>AWHC xx-0111-T</b>
X.X	±0.40	④	Add UL file no.	12.12.2013	Amy	Approved	14.02.2014	Amy	
X.XX	±0.25	③	Update	08.09.2011	Lucas				
X.XXX	±0.15	②	Update	29.06.2009	Dean				Drawing-No.
Angle	±3°	①	Update	25.01.2006	Alex				<b>ASS 2313 CO</b>
									rev05
		Id.	Modification	Date	Name			Replace	Sheet 1/1