



used for: D-SUB COMBINATION

NOTES:

1. METALSHELLS: STEEL; min. 320µ" TIN
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. THREADED INSERT: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
4. COLLAR: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
5. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
6. = CRITICAL DIMENSION; SPC

Directive 2002/95/EC
"RoHS"
Compliant

tolerance		scale: 2:1 (5:1)		material: SEE NOTES	
2001	date	name	D-SUB COMBINATION FEMALE 8W8S with threaded insert AutoCAD 2000 DIN-A 13K1A253A 3 sh: 1/1 part no: 3008W8SXX99A30X		
drawn	17.05.	Parei			
appd.	17.05.	E. Mickenbecker			
norm					
d-old					
DO NOT ALTER CAD DRAWING BY HAND		OWNERSHIP AND COPYRIGHT OF CONEC GMBH		THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.	
rev.	description	date	name		

