

## Specification Sheet

Part Number: T150L0K2



<b>Article Number</b>	111-15404
<b>Type</b>	T150L
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Heavy-duty design offers higher tensile strength.</li><li>• Buckle feature on head allows excess strap to be tucked away after installation.</li><li>• Bent tail ensures a quick and simple installation.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
<b>Short Description</b>	Heavy Duty Cable Tie, 32.3" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 50/pkg

Global Part Name

T150L-PA66-BK

Minimum Tensile Strength (Imperial)

175.0

Minimum Tensile Strength (Metric)

780.0

Length L (Imperial)

32.3

Length L (Metric)

820.0

Fixation Method

None

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.35

Width W (Metric)

8.9

Bundle Diameter Min (Imperial)

0.32

Bundle Diameter Min (Metric)

8.0

Bundle Diameter Max (Imperial)

9.6

Bundle Diameter Max (Metric)

243.8

Thickness T (Metric)

1.9

<b>Material</b>	Polyamide 6.6 (PA66)
-----------------	----------------------

**Material Shortcut** PA66

<b>US MIL SPEC</b>	MIL 53421	<b>Flammability</b>
--------------------	-----------	---------------------

UL 94 V2 **Halogen free**

Yes **Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C) **ROHS Complaint**

Yes **Certification/Specification WEB**

UL-ZODZ2.E64139 **UL Recognized (US)**

Yes **UL Recognized (US and Canada)**

Yes

<b>Package Quantity(Imperial)</b>	50
-----------------------------------	----

**Package Quantity (Metric)** 50

<b>Customs Number</b>	3926909987
-----------------------	------------

